

Product Update Notice

Upgraded IG2 LED Ingrade Up Light

New COB Light Engine.

More CCT & CRI choices.

More optics choices.

More lumen output.

Same quality and reliability.



Precision machined LED lighting fixture with 12V input LED Light Engine (COB with integrated driver module). Modular industry standard components allow for simple field replacement and future upgrade. Designed for in ground wet location installation for up lighting trees, landscapes, or any vertical hardscape / architectural surface.

Features ¹

- Industry standard COB LED components used to simplify maintenance and future upgrades.
- Field replaceable internal components and connectors on wiring connections for easy installation and maintenance.
- Light engine is enclosed in a water tight body that uses high temperature silicone O-rings and a water tight cable exit to ensure a wet location rating.
- Pour collar option allows for easy installation in concrete pour installations.
- Flush lens design reduces mineral deposits on lens surface.

Specifications ¹

- Input voltage: 12VAC (±10%).
- Lumen Output (nominal): 400lm, 700lm, 1000lm. ²
- Field replaceable optics: 15°, 24°, 36°, 55°, 65°.
- Color temperature: 2700K, 3000K, 3500K, 4000K.
- CRI options: 80, 90.
- Dimming: Phase dimming (ELV, MLV). ³
- L70 > 40,000 hours.
- Protection (driver): short circuit, overload, thermal, auto-reset.

1. Features and Specifications subject to change without notice. Please see latest specification sheet(s) on website for latest information.
2. Lumen Output (nominal) is ideal lumen output of light engine only in lab conditions. Actual fixture output will vary with fixture/cap type, material, lens/optics options, CRI, CCT, mounting, orientation, and environmental conditions. For more accurate information, see fixture photometry files on website.
3. Contact Vision3 for dimmer compatibility.