

## New Product Notice

### WM1 COB LED Wall Mount Light

Precision machined aluminum, brass, or stainless-steel LED lighting fixture available with 12V Integral Driver COB LED or Remote Driver COB LED (requires remote driver mount) light engine. Modular industry standard components allow for simple field replacement and future upgrades. Wet or dry location capable and certified for wall mount applications, the WM1 Wall Mount fixture is perfect for all interior, exterior, residential, commercial, retail, and hospitality uses.



#### Features<sup>1</sup>

- Industry standard COB LED components and wiring connectors to simplify maintenance and future upgrades.
- Field replaceable optics, COB, and driver.
- MR16 halogen, retro-fit MR16 LED, and amber turtle safe LED lamp options also available.
- High temperature silicone O-rings and molded silicone fixture lead seal to prevent leaking.
- Available in round and square shapes.
- Can be mounted pointing up or down.
- Tested and certified for wet or dry location use in interior or exterior wall mount applications.

#### Specifications<sup>1</sup>

##### Integral Driver COB LED

- Input voltage: 12VAC
- Lumen Output (nominal)<sup>2</sup>: 400lm, 700lm, 1000lm.
- Optics: 15°, 24°, 36°, 55°, 65°.
- CCT: 2700K, 3000K, 3500K, 4000K.
- CRI: 80, 90.
- L70 > 40,000 hours.
- Dimming<sup>3</sup>: ELV & MLV phase dimming.

##### Remote Driver COB LED

- Lumen Output (nominal)<sup>2</sup>: 1600lm @ 350mA,
- Optics: 15°, 24°, 36°, 55°, 65°.
- CCT: 2700K, 3000K, 3500K, 4000K.
- CRI: 80, 90.
- L70 > 40,000 hours.

1. Features and Specifications subject to change without notice. Please see latest specification sheet(s) on website for latest information.  
 2. Lumen Output (nominal) is ideal lumen output of light engine only in lab conditions. Actual fixture output will vary with fixture/cap type, material, lens/optics options, CRI, CCT, mounting, orientation, and environmental conditions. For more accurate information, see fixture photometry files on website.  
 3. Contact Vision3 for dimmer compatibility and dimming range.